

NITRORYD 2

FOR NITROGEN REJECTION



DESCRIPTION

NitroRyd 2 is manufactured for nitrogen rejection units and selectively adsorbs hydrocarbons, which allows nitrogen to be removed. This purification process allows natural gas streams to be more efficiently transported or further processed. This molecular sieve offers a wide selectivity and can help increase the value of natural gas streams.

- used to separate natural gas streams with high contents of nitrogen
- capable of removing nitrogen down to specification
- allows natural gas to be more easily transported and increases the stream's value
- offers an ideal selectivity for hydrocarbons over nitrogen

SPECIFICATIONS

NitroRyd 2			
Property	Unit	Pellets	
Diameter	mm	1.3 - 1.5	
Productivity for Nitrogen	Nm ³ /h.T	200; 220	240; 260
Crush Strength	N [per piece] (<i>lbm*ft/s²</i>)	≥100 (≥22.5)	≥80 (≥18)
Bulk Density	g/L (<i>lb/ft³</i>)	630-660 (39.3-41.2)	
Adsorption Pressure	Mpa	0.8	
Nitrogen Purity	%	≥99.5	
Nitrogen Recovery	%	≥40	
Adsorption Cycle	s	2x60	
Packaging Options	20kg (<i>44lb</i>) / plastic drum		

INDUSTRIES USED

nitrogen rejection units

natural gas conditioning

STORAGE

As an adsorbent, molecular sieve should not be left exposed to open air and should be stored in dry conditions with air-proof packaging.

CONNECT WITH US...

Hengye Inc.
 11999 Katy Frwy, Suite 588
 Houston, Texas 77079
Office (832) 288-4288
Fax (832) 288-4230
info@hengyeinc.com

